



Gas Fired Tandoori Oven

Instruction Manual

Company registered as
The Tandoor Clay Oven Limited in UK & Canada

www.PuriTandoors.co.uk / www.PuriTandoors.ca

Trading as **PURI Tandoors**



GAS FIRED TANDOOR OVEN



INSTALLATION AND OPERATOR INSTRUCTION MANUAL

FOR YOUR SAFETY:

1. Do not store or use gasoline or other flammable vapours or liquids in the vicinity of this or any other appliance.
2. A qualified installer must perform installation and service

WARNING: Improper installation, adjustment, alteration, service or maintenance can cause property damage, injury or death. Read the installation, operating and maintenance instructions thoroughly before installing or servicing this equipment.

WARNING: If you smell gas

1. Shut off gas to the appliance.
2. Extinguish any open flames.
3. Do not try to light any appliance.
4. Do not touch any electrical switch; do not use any phone in your building.
5. Immediately call you gas supplier from a neighbour's phone. Follow the gas Supplier's instructions.
6. If you cannot reach your gas supplier, call the fire department.

RETAIN THIS MANUAL FOR FUTURE REFERENCE: ASSEMBLER / INSTALLER: Leave these instructions with the appliance. A copy of these boxed instructions is to be posted in a prominent location and the instructions are to be followed in the event the user or area occupant detects gas odours.



Contents

1. Introduction	3
2. Consequential Loss	4
3. Installation introduction	4
3.1. Unpacking	6
3.2. Clearance and Positioning.....	6
3.3. Ventilation	7
3.4. Gas supply and connection	7
3.5. Start up and operation.....	8
4. User instructions.....	9
4.1. First firing.....	9
4.2. Shutting down of the appliance.....	10
5. Maintenance and cleaning of appliance	10
5.1. Servicing.....	10
5.2. General check	11
6. Component Replacement	11
6.1. Thermocouple	11
6.2. Ignite Electrode.....	12
6.3. Pilot Burner	12
6.4. Gas Tap Assembly	12
6.5. Burner	12
6.6. Injector/Orifice Spud.....	12
7. Technical Data.....	13
Warning Labels	14



1. Introduction

The manufacturer of this equipment, The Tandoor Clay Oven Limited has been in the business of manufacturing Tandoors since 2008 and has a world wide experience in the field of Tandoors for the last 8 years.

We provide tandoors of the highest quality using premium quality metal, component parts and clay. All of the Tandoors are CE, NSF &ANSI approved and therefore meet the highest safety standards laid down by the European & North American safety advisory. This product is for professional use and must only be operated by suitably trained personnel.

Its unique hygiene design makes the product extremely easy to clean and safe to use. As there are no exposed joints, the housing presents a flush surface that simplifies cleaning.

Please read the entire manual and follow all pertinent instruction when assembling, installing and operating this appliance. The manual should be retained for future reference. Please post in prominent location instructions to followed in the event user smells gas.

- Do not store or use flammable vapours or liquids in the vicinity of this or not any other appliance.
- Whilst in operation, parts of the appliance will become hot. Suitable precautions must be taken to avoid accidental burns.
- Keep all combustible products away from the Tandoor.
- This is gas fired Tandoor ONLY. No charcoal use. The oven must not be exposed to rain /water
- Keep at least 6" (150mm) away from any other equipment.
- Must be installed by a technically qualified technician.
- At all times keep this manual in the vicinity of the oven.

Warning:improper installation, adjustment, alteration, service or maintenance can cause property damage, injury or death. Read the following installation, operation and maintenance instructions thoroughly before installing or servicing this equipment.

Continuous product improvement is a policy of The Tandoor Clay Oven Limited. Specification and designs are subject to change without notice.



2. Consequential Loss

The Tandoor Clay Oven Limited does not accept responsibility for loss of food, production time, production time, Profit etc, which may result from the breakdown of the appliance.

Models of this tandoor oven suitable for installations in North America, (Canada or the U. S. A.) display a special marking plate with the ETL logo on the name plate and a reference on the plate to ANSI Z83.11 Standard to indicate compatibility to gas connections devices used in those countries.

These North America designated appliances are suitable for use only on natural gas. For any Canadian or U.S.A installations, only the correct version of this appliance can be used and these can be only operated on natural gas.

This appliance must be installed in accordance with current local regulations and only used in a well ventilated area.

3. Installation introduction

This product is made with the safest materials conforming to the United States NSF and according to the relevant CE directives. Proper installation must conform to all local codes. Within Europe, appliances should be installed in accordance with BS6173: 2009 code of practice for installation of gas catering appliances, taking into account Gas Safety (Installation and Use) Regulations 1998 Approved Code of Practice and guidance and Health and safety at Work Act 1974.

For Canada and the U. S. A. -When installing this appliance, please refer to all applicable codes or, in the absence of local codes, (In the U.S.A.) follow the National Fuel Gas Code, ANSI Z223.1/NFPA 54. In addition, ANSI / NFPA 96 – (latest edition), covering the installation of equipment for the removal of smoke and grease-laden vapours from commercial cooking equipment must be conformed to.

BEFORE STARTING WITH THE INSTALLATION OF THE APPLIANCE, PLEASE READ AND BE FAMILIAR WITH THE INFORMATION IN THIS MANUAL

Installation of this must be performed by a registered gas –safe gas fitter or in the U.S.A, a qualified installer.

- **Appliance installation sites should be provided with safety instructions based on information supplied by local fuel suppliers. These instructions are to be posted in a prominent area near the appliance.**
- **All installations are to conform to local codes. In the absence of local codes, installation should conform to the National Fuel Gas Code, ANSI Z223.1/NFPA 54, and in Canada the National Gas Installation Code, CAN/CGA-B149.1**



- The appliance and its individual shutoff valve must be disconnected from the gas supply piping system during any pressure testing of that system at pressures in excess of psi (3.45kPa).
- The appliance must be isolated from the gas supply piping system by closing its individual manual shutoff valve during any pressure testing of the gas supply piping system at test pressures equal to or less than 1/2 psi (3.45 kPa). In Europe a gas soundness test must be carried out.
- Oven is to be caster mounted for use: The installation shall be made with a connector that complies with the Standard for Movable Gas Appliances, ANSI Z21.69CSA 6.16, and a quick disconnect device that complies with the Standard for *Quick-Disconnect Devices for Use With Gas Fuel*, ANSI Z21.41CSA 6.9. Adequate means will be provided on site to limit the movement of the oven without depending on the connector and the quick-disconnect device or its associated piping to limit the appliance movement.
- The rear panel on the tandoor oven has a fastener location suitable for attachment of restraint devices. The fastener is identified with a marking tag.
- Do not allow untrained operators to use this equipment.
- Exercise extreme care in handling metal parts. Do not touch any metal or other surfaces that become hot in operation.
- **NO ATTEMPT SHOULD BE MADE TO OPERATE THIS APPLIANCE DURING AN ELECTRICAL POWER FAILURE.** In the event of the loss of electrical power, exhaust hood will not function. If this happens turn off the hood power switch and turn off the gas tandoor oven valve (s).
- **IF INSTALLATION SITE IS PROVIDED WITH A POWER LOSS INTERLOCK DEVICE, IT WILL ACT TO SHUT OFF ALL GAS IN THE EVEN OF ELECTRICAL POWER FAILURE. FOLLOWING LOSS OF POWER MANUAL RELIGHT OF PILOT BURNER WILL BE REQUIRED.**
- Refer to local codes for the building fresh air supply requirements. For the U. S. A., in the absence of local codes, refer to the National Ventilation Code entitled, "Standard for the Installation of Equipment for the Removal of Smoke and Grease laden Vapors from Commercial Cooking Equipment", NFPA-96-latest edition.
- **Note: Where servicing may require greater access clearances than those shown on the nameplate, then the greater clearances should be allowed for.**
- At installation, adequate clearances should be provided for proper operation and servicing of the appliance and any field installed optional items. Data plate applies only to tandoor oven as provided by appliance manufacturer
- **This appliance is for installation only at the clearances indicated on the name plate. Clearances are specified from combustible and for non-combustible construction.**



- **Observe clearances from combustible surfaces as marked on name plate. Clearances posted on unit are for safety reasons and lesser clearances cannot be applied. Additional clearances might be required for service and operator access.**
- **Do not block any louvered openings on appliance service panels.**

3.1. Unpacking

- Un- crate the unit with extreme care, do not use a hammer or heavy tools to un- crate the unit. Always remove shipping container parts and panels by only outward prying.
- Make sure the unit is in the upright position before starting to un- crate.
- **Before fixing the appliance in place, remove all protective plastic coating from the unit.**
- Oven is on 4" (100mm) wheel castors and can be rolled out easily to the designated installation area.
- Unit must be rolled around by hand. Do not use a lift jack.

3.2. Clearance and Positioning

- This appliance requires a 6" (150mm) clearance from combustible and non-combustible material and surfaces.
- Never install propane appliances below grade.
- A clear space, (rear clearance) of at least 6" (150mm) should be maintained at the rear and sides of the appliance.
- There must be minimum clearances of 32" in the US and (750 mm in Europe) between top of the appliance and any overhanging shelf. Shelves must be of non-combustible material.
- It is recommended that the appliance is not installed in draughty locations or near doors.
- If the appliance is positioned on a combustible floor, sheet material (preferably stainless steel) equal to the base area of the appliance must be secured to the floor prior to fixing the appliance in place. **NOTE: For Canadian and U. S. A. installation is authorized only on non-combustible floors.**
- Ensure that the appliance is level.
- Inspect for damage. If any damage is noted, report damage to the freight company and contact manufacturer at the address shown on the cover.



- Verify that the unit marking plate indicates that the unit is set up for service on the type of gas fuels as found at the installation site. Natural gas units have to be operated on natural gas only and propane units used only on propane gas.
- Plan location of units in such a manner as to be best accessible to operator. Locate unit so that foot traffic in area will not interfere with unit operation. When choosing unit location, take into consideration the operation of overhead and side mounted heating/cooling ducts and fans

3.3. Ventilation

- The area in which the appliance is to be installed should have sufficient fixed ventilation to comply with the requirements of Approved Document J in the 1985 Building Regulations in Europe, with a minimum area of 4.5 cm per 1Kwh (3412Btu per hr) of total heat input.
- Ventilation hood must be installed above the appliance according to all appliance codes by your local and state health and fire regulations.
- It is required that the Tandoor be interlocked to the hood ventilation system.
- There must be sufficient low-level ventilation to ensure that the appliance has a good supply of clean fresh air.

3.4. Gas supply and connection

- Check that the gas supply correspondence to that on data plate. Gas connection must be the same size of the PURI Tandoors, BSP ½", (For U. S. A. and Canada NPT ½"). Inlets. Warning: Do not under any circumstances join NPT to BSP threads when making connections.
- The ½" connection for connection of gas supply is located behind the unit.
- A shut off valve should be installed on the gas service line ahead of the unit in case of emergency and for serving purposes. The location of the manual shutoff valve should comply with codes in effect at the installation site.
- **Since the appliance is caster mounted, connection of the appliance must be made using suitable flexible connection devices.** Ensure that the hose is suitable for commercial catering appliances and a restraining wire and wiring label are used.
- Fixed pipe work must not be used with this appliance.
- For the U. S. A. and Canada - Installation shall be made with a connector that complies with the standard for connectors for Movable Gas Appliance, ANSI Z21.69- CSA6.16, and a quick Disconnect devices for the use with gas fuel, ANSI Z21.41- CSA 6.9.



- Connect tandoor to gas supply and conduct gas leakage tests to verify gastight connections. Check entire piping system for leaks. A solution consisting of 50% dishwashing detergent and water mix can be applied to all piping parts with a brush.
- Matches, candles or other sources with open flames or sparks shall not be used for this purpose. Gas controls are provided with outlet settings suitable for the fuel type shown on the name plate. Adjustments, if needed, to the regulator should only be made by qualified service staff. The regulator outlet pressure must be the pressure shown on the name plate for the type of gas fuel used.
- Some local codes require that a manual shutoff valve be installed in the same room and within six feet of the appliance. If because of local code requirements, a manual gas shutoff valve has to be installed on the appliance, and if it is mounted inside of enclosure by access doors, a label should be provided indicating this construction.
- Proper gas piping: In order to insure proper performance of this unit as well as other gas appliances on the same gas supply lines, a well-planned and properly sized gas supply system is a must. If the appliances are to be connected to existing piping, the piping should be checked for adequate capacity enabling full firing for all of the units that are to use the piping run.
- Pipe thread sealant (joint compound) shall be used sparingly and only on male threads of pipe joint. Such compounds shall be resistant to the action of L.P. gases.
WARNING: All pipe fittings must be clean and free of dirt or other contaminants. Any loose particles, such as dirt or metal filing, in gas lines can damage the controls and affect operation.
- Make certain not to obstruct the flow of combustion and ventilation air. Insure that air intake openings around the appliance jacket are not obstructed.
- Appliance must be connected to suitable exhaust duct in compliance with all applicable local codes.
- Position the appliance to insure that proper clearances for safety and service are provided.

3.5. Start up and operation

All appliances are operationally checked and adjusted before leaving our factory. These adjustments are made to verify effective operation and that the appliance meets the requirements of the tests standards. At the installation site making sure all local codes are met is the responsibility of the installer.

Puri Tandoors uses a safety pilot system to ignite the burner and monitor flames and to shut off the gas supply in case of loss of burner or pilot flames. The gas supplies to the



pilot and burner are fed through a thermo- magnetic safety valve. A thermocouple is part of the safety systems and it functions to hold the gas valve open after a proper pilot flame is established.

Before firing of unit, fit burner plate over burner and place a layer of rocks evenly and level onto plate. Only use rocks as supplied with the appliance.

4. User instructions

- Make sure that the manual shutoff valve behind the unit is turned off and that the Tandoor gas valves are turned off.
- Open the main gas line to the Tandoor oven.
- On the appliance control valve depress and hold the back knob on the star position indicated by a star for 10 seconds to start pilot gas flow and to clear the air from the gas line.
- Repeatedly push the piezoigniter until the pilot burner lights. (the pilot light can be seen faintly at 5 o' clock below the burner plate)
- Continue to keep the control knob pressed in for a further 20-30 seconds for the flame sensing device to establish itself.
- If the pilot burner extinguishes itself when the knob is released, repeat the above procedure.
- If the burner extinguishes for the any reason while the oven is operating, switch control off and **WAIT 5 MINUTES BEFORE RELIGHTING**. If for any reason burners become extinguished, repeat lighting instructions beginning with Step 1.
- After the pilot burner is lit main burner can be turned on. To do so rotate the control knob anticlockwise, (counter clock). The burner can now be set to high flame position indicated by the large flame symbol. To adjust flames to lower flame setting, turn knob to the low position, or anywhere between the two, continue to turn the control knob anti- clock wise towards the small flame symbol.
- The main burner should light smoothly and quietly. Burner flames should be predominantly blue.
- When not in use, the control knob should always be set to the **OFF** position.

4.1. First firing

It is important to gradually build up heat within the Tandoor the first time it's being used. **The burner should be at very low setting (control valve set at LOW) for at least 6 hours before gradually increasing the flame intensity.**



During this procedure the mouth of the Tandoor should be completely exposed. **DO NOT cover the opening with the stainless steel lid.** Do not be alarmed if you see small fissures appear on the clay surface it will not affect the performance of the Tandoor.

4.2. Shutting down of the appliance

To turn off the appliance, turn the control clockwise until the indicator on the knob is in the off position indicated by the black dot symbol. Visually confirm that the flames have gone out.

WARNING- after the operation the appliance will remain hot for sometime, therefore, to avoid injury, care should be taken to prevent contact with hot surfaces.

5. Maintenance and cleaning of appliance

Routine Maintenance - Slight hairline cracks are expected to appear in the clay pot during use. A tub of fire cement (furnace cement), is supplied with the oven to effect repairs as follows (when the Tandoor has cooled down):

- Dampen the affected area with a moist cloth.
- Fill in the crack with the fire cement using a wooden spatula.
- Smooth the foiled area with a soft moist cloth.
- Allow repair to air dry for approximately 6 hours. **DO NOT WET THE CLAY LINING.**
- Remove rocks and lightly brush clean.

Normal Cleaning - Clean all the external panels with a non-abrasive detergent. To safely remove the build-up of grease on the clay surface, wipe it down with a cloth that has been dampened with a solution of salt and white vinegar.

5.1. Servicing

The tandoor oven should be routinely serviced to ensure a long trouble free life. It is recommended that the appliances are serviced every 6 months by a registered gas –safe fitter/qualified person.

In the event that the ignition is delayed or becomes noisy, turn off the appliance and call for a service.



5.2. General check

Remove the control knob and the 4 screws securing the front cover and cover off over the tap spindle.

1. General check of the appliance, e.g. installation, ventilation, gas connections, gas supply fittings/flexible hose, restraint wire fitted isolation shut off valve.
2. Check low flame setting, adjust as necessary.
3. Check general burner condition. Clean burner ports with vacuum cleaner or low pressure air.
4. Clean aeration port/air shutter opening and injector of any lint build-up.
5. Carry out gas soundness /gas leakage test.

WARNING: Components after cleaning should be replaced in reverse order of removal and verified to be correctly positioned before Tandoor is fired. If any parts are damaged or lost during cleaning, do not operate unit until they are replaced. To do so will void warranty.

6. Component Replacement

1. Only qualified persons should conduct service or repair of this equipment.
2. Always disconnect power and fuel when repairing or servicing these appliances.
3. Any service or repair conducted on the unit as covered by the warranty has to be authorized by the manufacturer.
4. Only the original factory parts are to be used for any repair or replacement.
5. If parts are lost or missing, obtain and install replacement parts before returning unit to service.
6. Following service, be sure to reconnect all parts, and close all panels and covers before power is turned back on. Do not attempt to bypass any safety controls. Doing so voids warranty and creates dangerous operating conditions.
7. Access to service most components is gained by removing of the front cover. This is done by undoing the screws which secure the front cover and then removing cover.

6.1. Thermocouple

1. Loosen the thermocouple and pilot gas supply connection to the valve.
2. Undo the nut holding the pilot light assembly cradle and withdraw.
3. Replace the thermocouple.
4. Replace as above in reverse order.



DO NOT OVERTIGHTEN THE CONNECTION VALVE

The tip of the thermocouple should be 1" (25 mm) from the edge of the main burner and level with the top of main burner.

The pilot flame should completely envelope the tip of the thermocouple.

6.2. Ignite Electrode

1. Remove the igniter lead from piezo.
2. Undo the nut holding the light assembly cradle and withdraw.
3. Replace the electrode.
4. Replace as above in reverse order.

6.3. Pilot Burner

1. Loosen the thermocouple and pilot gas supply connection to the valve.
2. Undo the nut holding the pilot light assembly cradle/bracket and replace.

6.4. Gas Tap Assembly

1. Loosen and remove connections to burner pipe and gas inlet pipe
2. Loosen and remove connections to pilot burner.
3. Loosen connection to thermocouple and remove.
4. Loosen and remove the holding plate nut
5. Withdraw tap/valve assembly
6. Replace as above in reverse order

6.5. Burner

1. Remove rocks and plate sitting on the burner.
2. Loosen connection from burner pipe to gas tap/valve and remove.
3. Withdraw burner through top of oven.
4. Replace as above in reverse order.

6.6. Injector/Orifice Spud

1. Loosen connection from burner pipe to gas tap/valve and remove.
2. Loosen and remove injector/orifice spud carrier from burner.
3. Loosen and remove injector/orifice spud from injector carrier.
4. If necessary clean out injector with fine wire or air hose.
5. Replace as above in reverse order.



7. Technical Data

UK & European Units

	NATURAL GAS	PROPANE GAS (LPG)
Heat input	10 kW (net) 35000 Btu	10 kW (net)
Gas Pressure	20 mbar	37 mbar
Burner Pressure	High rate 15-16 mbar	35-36 mbar
	Low rate 6-7 mbar.	26-27 mbar
Gas rate	0.95 m ³ /hour	0.72kg/hour

North American Units

	NATURAL GAS ONLY
Heat input	48,000 BTU/Hr.
Inlet Gas Pressure	7" wc
Maximum Inlet Gas Pressure	10.5" wc
Minimum Inlet Gas Pressure	4" wc
Manifold Pressure	5.5" wc



Warning Labels

WARNING: Improper installation, adjustment, alteration, service or maintenance can cause property damage, injury or death. Read the installation, operating and maintenance instructions thoroughly before installing or servicing this equipment

NOTICE: In order to be able to service this appliance, it must be installed with the casters supplied, a connector complying with CE and a quick disconnect device complying with CE. It must also be installed with the restraining means to guard against transmission of strain to the connector as specified in the appliance manufacturer's instructions.